




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : F16K 31/06	A1	(11) International Publication Number: WO 95/00787 (43) International Publication Date: 5 January 1995 (05.01.95)
(21) International Application Number: PCT/US94/07303 (22) International Filing Date: 28 June 1994 (28.06.94) (30) Priority Data: 08/084,814 28 June 1993 (28.06.93) US (71) Applicant: AURA SYSTEMS, INC. [US/US]; 2335 Alaska Avenue, El Segundo, CA 90245 (US). (72) Inventors: MORINIGO, Fernando, B.; 8837 Glider Avenue, Los Angeles, CA 90045 (US). BLAIRE, William, C.; 8230 Canterbury Way, Buena Park, CA 90620 (US). BULGATZ, Dennis; 6522 Yarmouth Avenue, Reseda, CA 91355 (US). (74) Agent: CLIFFORD, Lisa, A.; Aura Systems, Inc., 2335 Alaska Avenue, El Segundo, CA 90245 (US).		(81) Designated States: CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: IMPROVED CORE DESIGN FOR ELECTROMAGNETICALLY ACTUATED VALVE**(57) Abstract**

An improved electromagnetically actuated valve (10) is disclosed. The improved valve design includes a layer of structurally stable, non-magnetic material (52), preferably Kapton or Chrome, disposed intermediate the core element (16) and the electromagnetic element (32, 34) of the valve, and a core element and electromagnetic element fabricated from a high electrical resistive iron material. The layer of non-magnetic structurally stable material and high resistance core element serve to eliminate the hysteresis effect in the magnetic force of the valve. The core element may also include radially extending (50) or axially extending (48) perforations through the core element. The axial and radial perforations serve to reduce the weight of the core design and the axial perforations serve to reduce the effect of the air spring created in the gap as the core element approaches the electromagnetic element during operation of the valve.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

IMPROVED CORE DESIGN FOR ELECTROMAGNETICALLY ACTUATED VALVE

5

RELATED APPLICATION DATA

The present application is a continuation-in-part of commonly owned, co-pending application U.S. Serial No. 07/957,194, filed on October 5, 1992 for
10 Electromagnetically Actuated Valve, which is incorporated by reference herein.

FIELD OF THE INVENTION

15

The present invention relates generally to an electromagnetically actuated valve, and more particularly to an improved core design for an electromagnetically actuated valve.

20

BACKGROUND OF THE INVENTION

In the past, valves have been designed for opening and
25 closing mechanisms that combine the action of springs with electromagnets. However, the earlier designs did not operate quickly enough to open and close the valves with sufficient speed. For example, valves using spring action could not be designed with the speed normally required for
30 the opening and closing of an internal combustion engine's intake and exhaust valves, or for the speed required for air

compressors.

One of the reasons why the earlier valve designs could not operate at the desired high speeds is the mass of the moving core assembly. In previous designs, the mass of the moving core piece providing the return path for the magnetic flux was not sufficiently small so that it could be accelerated as quickly as desired for certain applications, such as modern internal combustion engines. Therefore, a need existed for a lightweight core design for use in an electromagnetically actuated valve.

Another problem with the valves of the prior art is caused by hysteresis, or a lagging in the value of magnetization in a magnetic material due to a change in magnetizing forces. More specifically, in the previously designed electromagnetic actuators, eddy currents and a residual flux remain in the magnetic material when the electromagnet in the valve is deenergized, causing a delay in the release of the core and therefore a decrease in the speed of the valve. Therefore, it is desirable to eliminate the residual flux, and thereby instantaneously decay the magnetic forces to zero such that the actuator reacts quicker.

SUMMARY OF THE INVENTION

Accordingly, it is a primary object of the present invention to overcome one or more disadvantages and limitations of the prior art.

Another object of the present invention is to provide electromagnetic actuator having a sufficiently small moving core mass to allow valve operation at higher speeds and higher frequency than the prior art.

Still another object of the present invention is to provide electromagnetic actuator that reduces the hysteresis effect on the actuator magnetic forces.

10

According to a broad aspect of the present invention, the design of the core element of the electromagnetic actuator is improved. The electromagnetically actuated valve includes at least one electromagnetic assembly having an electromagnetic element and a coil disposed within the electromagnetic element, and at least one core element defining a central axis and being biased in an initial spaced apart relationship from the electromagnetic elements. The improvement comprises a layer of structurally stable, non-magnetic material disposed intermediate the electromagnetic elements and the core element. Another aspect of the invention is that the core element defines at least one aperture offset from the central axis. In the embodiment shown, the core element includes both radially and axially oriented apertures.

25

These and other objects, advantages and features of the present invention will become readily apparent to those skilled in the art from a study of the following description of an exemplary preferred embodiment when read in conjunction with the attached drawing and appended claims.

30

BRIEF DESCRIPTION OF THE DRAWINGS

5 Figure 1 is a cross-sectional view of one embodiment of the electromagnetically actuated valve showing the apertures of the improved core design and the layer of non-magnetic material of the present invention;

10 Figure 2 is a top view of the improved core design of the electromagnetically actuated valve of the present invention; and

15 Figure 3 is a side view of the improved core design of the electromagnetically actuated valve of the present invention.

DESCRIPTION OF AN EXEMPLARY PREFERRED EMBODIMENT

20 Referring now to Figure 1, one embodiment of a valve 10 of the present invention is shown in cross-section. In the embodiment shown, the valve 10 includes two pairs of electromagnetic elements 12, a plurality of coils 14, a core element 16, a support spring 20, a valve stem 22, and a valve case 24. Each of the electromagnetic elements 12 preferably have an annular shape. The annular shape of the electromagnetic elements 12 defines a central chamber 26 through which the valve stem 22 extends. The central
25 chamber 26 further defines a central vertical axis 28 of the core element 16.
30

The electromagnetic elements 12 each define two open faces 36, which lead into a central channel 30 within the electromagnetic elements 12. The open faces 36 provide an electromagnetic pole face area. The coil elements 14 extend within the channel 30 of the electromagnetic elements.

Each pair of electromagnetic elements 12 further comprises an upper electromagnetic element 32 and a lower electromagnetic element 34. The upper and lower electromagnetic elements are in a mirrored relationship to each other, with the central channels 30 of the upper and lower electromagnetic elements being in a facing relationship to each other.

Disposed intermediate the upper and lower electromagnetic elements 32, 34 is the core element 16. The core element 16 provides a pole face area 41. In the embodiment shown, the core element 16 is secured to the valve stem 22, preferably at the center of the core element 16. The valve stem 22 preferably extends in axial alignment with the central vertical axis 28 of the central chamber 26

25

The support spring 20 is also disposed within the central chamber 26, preferably surrounding the valve stem 22. The valve is enclosed by the valve case 24, which defines an upper portion 38 and a lower portion 40 that the support spring 20 contacts.

30

Referring now to Figures 1, 2 and 3, the advantages of the unique core design of the present invention are discussed. As shown in Figure 1, the core element 16 may include an upper surface 42, a lower surface 44 and an outer edge surface 46 connecting the upper and lower surfaces. The core element 16 includes a plurality of axially extending apertures 48 which extend from the upper surface 42 to the lower surface 44 of the core element 16. In the embodiment shown in Figures 2 and 3, eight axially extending apertures 48 are disposed equidistant around the circumference of the core element 16. Each of the axially extending apertures 48 are disposed approximately one-quarter of an inch from the outer edge of the core element 16.

The axially extending apertures 48 serve two purposes. The first purpose is to reduce the mass of the core element 16, while still providing a sufficient flux path area. Therefore, the axially-oriented apertures 48 allow for faster operation of the valve. The second purpose of the axially-extending aperture 48 is to allow air to pass through the core element 16 as the core element approaches the electromagnetic elements 32,34. This, in turn, reduces the air spring effect created between the core element and the electromagnetic elements during operation of the valve.

The core element 16 further includes sixteen radially extending apertures 50 arranged equidistant around the circumference of the core element 16. The radially extending apertures 50 preferably extend from the outer

7

edge surface 46 approximately one-quarter of an inch towards the central axis 28. The radially extending apertures also serve to reduce the mass of the core element.

5

It should be noted that the described quantity, dimensions, and locations of the apertures 48, 50 used in the preferred embodiment are exemplary only, and that a different quantity, dimension and location of apertures could be used for this invention. It is also noted that the shape of the core element is exemplary only. For example, the core element, disclosed in U.S. Patent Application No. 07/957,194, filed on October 5, 1992 and assigned to the assignees herein, may be designed with apertures which extend through the core element at an angle from the central vertical axis of the core element.

Referring now to Figure 1, another feature of the present invention is shown. As shown in Figure 1, the actuator includes a thin layer 52 of non-magnetic, structurally stable material disposed intermediate the electromagnetic elements 32, 34 and the core element 16. The thin layer 52 is preferably comprised of Kapton or Chrome. The layer 52 of material is preferably approximately 2-3 thousandths of an inch in thickness. In Figure 1, the layer 52 is shown as coated on the pole face areas of the electromagnetic elements 32, 34, such that the coating is intermediate the electromagnetic element and the core element when the valve is closed. Referring now to Figures 2 and 3, the layer 52 of non-magnetic material may also be coated directly onto the core element 16. The

coating of the non-magnetic material onto the core element also allows the layer 52 of material to be disposed intermediate the electromagnetic element and the core element when the valve is closed.

5

The function of the layer 52 of non-magnetic material is to reduce the inductance at the smallest gap. More specifically, when the valve is closed, and the electromagnetic element contacts the core element, a closed flux path is created between the electromagnetic element and the core element. However, when the current is turned off, eddy currents develop to oppose change in the field. Therefore, the magnetic field does not immediately decay to zero, and flux continues to exist and create force. Therefore, the magnetization value in the valve undergoes a lagging effect in the magnetization force applied to the valve.

In order to eliminate the eddy currents when the electromagnet is deenergized, it is necessary to minimize the value of decay time in the magnetic field. In the present invention, this is accomplished by reducing the inductance at the smallest gap and increasing the resistance of the material in the core element. More specifically, the inductance is decreased by disposing the layer 52 of non-magnetic, structurally stable material intermediate the core element and the electromagnetic element. The layer 52 is preferably a thin layer so as to not significantly effect the output of the valve. The layer 52 creates a gap between the electromagnet and core element which decreases the inductance of the magnetic field.

To further reduce the decay time, it is desirable to increase the electrical resistivity of the core element and electromagnetic element material. In the preferred embodiment of the present invention, a high electrical resistivity iron is used to fabricate the core element and electromagnetic element. By way of example, silicon iron may be used for the core element and electromagnetic element. Therefore, in operation, when the electromagnet is deenergized, the low inductance of the gap created by the layer 52 and the high electrical resistivity of the core element and electromagnetic element material will expedite the decay of the magnetic forces to zero, allowing the actuator to react quicker.

15

Referring back to FIG 1, the operation of the valve 10 will be described. It is to be noted that in this context, the core assembly 16 includes the core and the assembly connected to the core for each particular application. In its neutral, unpowered state, the spring 20 hold the core 16 halfway between the upper and lower electromagnets 32, 34, in the equilibrium position. In order for the valve 10 to change from the neutral position to the closed position, a high current short duration pulse is applied to coil 14a, creating an electromagnetic force that attracts the core 16 to the upper electromagnet 32. The electromagnetic force overcomes the forces of the spring 20 and therefore drives the valve 10 to its closed position. Once the valve 10 is in its closed position, only a small steady current in the coil 14a is necessary to maintain the valve 10 in its closed position.

30

The core 16 remains in the closed position as long as the attractive force between the core 16 and the electromagnet 32 is greater than the force with which the spring 20 tries to restore the core 16 to its neutral position. In order to open the valve 10, the current flowing through the coil 14a is interrupted. When the current is interrupted, the spring 20 drives the core assembly 16 back toward the neutral position, gaining speed as it approaches the neutral position. The net force of the spring 20 on the core assembly 16 is zero at the neutral position, however, by Newton's law of motion, at maximum velocity. The velocity, therefore, carries the core assembly 16 past the neutral position. Once the core assembly 16 is past the neutral position, the spring 20 exerts forces on the core assembly 16 opposing the velocity, which decelerates the core assembly 16 as it approaches the lower electromagnet 34.

In the case of very small friction, the moving core assembly 16 will move past the neutral position to a distance from the neutral position approximately equal to the distance from the neutral position from which it started on the opposite side. As the core assembly 16 approaches the lower electromagnet 34, a relatively small current in the coil 14b is sufficient to provide a force to compensate for energy lost due to the mechanical friction and spring damping and to add the energy required to overcome the pressure differential across the valve. The current in coil 14b is also sufficient to hold the valve in the open position.

When the valve 10 is in its operational powered state, the energy required to drive the valve 10 from the open position to the closed position, or vice versa, is furnished almost entirely by the energy stored in the compressed support spring 20. A small amount of energy lost to friction is provided by the attraction of the core assembly 16 to the lower electromagnet 34, which begins as soon as the current is turned on in the coil 14b. Thus, preferably the coil 14b is turned on early in the valve opening sequence, closely following the interruption of the current in the coil 14a.

It should be noted that it is also possible to utilize the valve of the present invention in order to actuate an external load. In this embodiment of the invention, the valve stem is comprised of an actuator rod, which is connected to the external device. The upper and lower electromagnetic elements are then energized sequentially at a resonant frequency, in order to resonate the spring mass system. Therefore, the actuator actuates the external load, while maintaining a low current requirement.

There has been described hereinabove an exemplary preferred embodiment of the electromagnetically actuated valve according to the principles of the present invention. Those skilled in the art may now make numerous uses of, and departures from, the above-described embodiments without departing from the inventive concepts disclosed herein. Accordingly, the present invention is to be defined solely by the scope of the following claims.

THE CLAIMS

I claim as my invention:

- 1 1. In an electromagnetically actuated valve having
2 at least one electromagnetic assembly including an
3 electromagnetic element and a coil disposed within the
4 electromagnetic element, and at least one core element
5 defining an upper surface, a lower surface, an outer edge
6 surface and a central axis and being biased in an initial
7 spaced apart relationship from the electromagnetic
8 element, an improvement comprising:
9 a layer of structurally stable, non-magnetic material
10 disposed intermediate the electromagnetic element and the
11 core element; and
12 at least one radial aperture extending radially at least
13 partially through the core element intermediate the upper
14 surface and the lower surface.
- 1 2. An electromagnetically actuated valve in
2 accordance with Claim 1 wherein said layer of structurally
3 stable, non-magnetic material is coated onto the core
4 element.
- 1 3. An electromagnetically actuated valve in
2 accordance with Claim 1 wherein said layer of structurally
3 stable, non-magnetic material is coated onto a portion of
4 the electromagnetic element.
- 1 4. An electromagnetically actuated valve in
2 accordance with Claim 1 wherein said layer of material is
3 comprised of Kapton.
- 1 5. An electromagnetically actuated valve in

2 accordance with Claim 1 wherein said a layer of material is
3 comprised of Chrome.

1 6. An electromagnetically actuated valve in
2 accordance with Claim 1 wherein said layer of structurally
3 stable non-magnetic material is approximately 2-3
4 thousandths of an inch in thickness.

1 7. An electromagnetically actuated valve in
2 accordance with Claim 1 wherein the improvement further
3 comprises the core element and electromagnetic element
4 being fabricated from a high electrical resistivity material.

1 8. An electromagnetically actuated valve in
2 accordance with Claim 7 wherein the high resistivity
3 material is silicon iron.

1 9. An electromagnetically actuated valve in
2 accordance with Claim 1 wherein the improvement further
3 comprises the core element defining at least one non-
4 radially oriented aperture, said non-radially oriented
5 aperture being offset from the central axis of the core
6 element.

1 10. An electromagnetically actuated valve in
2 accordance with Claim 9 wherein the diameter of said
3 aperture is approximately one-eighth of an inch.

1 11. In an electromagnetically actuated valve having
2 an electromagnetic element, a coil disposed within the
3 electromagnetic element, and an annular-shaped core
4 element having an upper surface, a lower surface and an
5 outer edge surface, and defining a central axis, and being

6 biased in a normally spaced apart relationship from the
7 electromagnet, an improvement comprising:

8 said core element defining at least one radial aperture
9 extending radially at least partially through the core
10 element intermediate the upper surface and the lower
11 surface.

1 12. An electromagnetically actuated valve in
2 accordance with Claim 12 wherein said radial aperture
3 begins at the outer edge surface of the core element.

1 13. An electromagnetically actuated valve in
2 accordance with Claim 13 wherein said radial aperture
3 extends approximately five-sixteenths of an inch toward
4 the central axis from the outer edge surface of the core
5 element.


1 14. An electromagnetically actuated valve in
2 accordance with Claim 12 wherein the diameter of said
3 radial aperture is approximately one-eighth of an inch.

1 15. An electromagnetically actuated valve in
2 accordance with Claim 12 wherein said core element
3 further defines at least one axially oriented aperture, said
4 axially oriented aperture being offset from the central axis.

1 16. An electromagnetically actuated valve in
2 accordance with Claim 16 wherein the diameter of said
3 axially oriented aperture is approximately one-eighth of an
4 inch.

- 1/2 -

FIG. 1



- 2 / 2 -

FIG. 2





FIG. 3

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US94/07303

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) :F16K 31/06

US CL :251/129.1, 129.15, 129.16, 368

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 251/129.1, 129.15, 129.16, 368

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US, A, 5,048,564 (GIARDO) 17 September 1991, See the entire document.	1,3,4,6,7
A	US, A, 4,951,878 (CASEY) 28 August 1990, col. 5, lines 18-20.	7, 8
A	US, A, 4,655,396 (TAXON) 07 April 1987, col. 3, lines 48-52.	5
A	US, A, 4,830,286 (ASSLAENDER) 16 May 1989, See the entire document.	9



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

A

document defining the general state of the art which is not considered to be of particular relevance

E

earlier document published on or after the international filing date

L

document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O

document referring to an oral disclosure, use, exhibition or other means

P

document published prior to the international filing date but later than the priority date claimed

T

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z

document member of the same patent family

Date of the actual completion of the international search

21 SEPTEMBER 1994


Date of mailing of the international search report

07 NOV 1994

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer


ROBERT G. NILSON

Telephone No. (703) 308-2602

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US94/07303**Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)**

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☒ Claims Nos.: 12-16
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:

Claims 12-16 because claims 12, 13, and 16 are dependent upon themselves and claims 14 and 15 depend from claim 12. See Rule 6.4(a).
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

☐
☐

- The additional search fees were accompanied by the applicant's protest.
- No protest accompanied the payment of additional search fees.